TE1590R-D
15”Resistive Touch Monitor

TouchSystems

Medical | Education | Government | Corporate

At a Glance

- Ergonomic Touch
- Resistive
- 15”Panel
- Easy to Clean and Use
- Various Mounting Options

TE1590R-D
5-Wire Resistive

The TouchSystems TE 15”Resistive Touch monitor combines elegance with durability. With its dust- and splash-proof bezel design, it is meant for public and high-use application. The TE 15”Resistive Touch monitor also comes with versatile mounting options, allowing it to fit in almost any environment. The monitor is HID compliant, allowing for integration with thin clients or computers, and it is equipped with a lockable OSD button and eight-language support.

Medical
The TE 15”Resistive Touch monitor is easy to clean and features a dust- and splash-proof design.

Government
The monitor’s versatile mounting options allow it to be placed in locations ranging from senate chambers to the local DMV.

Education
The TE1590R-D’s structure and dust- and splash-proof design is perfect for any classroom, cafeteria, or service area.

Corporate
The TE 15”Resistive Touch monitor offers both a beautiful design and display and a sturdy structure.

Specifications

Viewable Image Size	15”
Touch Technology	Resistive
Pixel Pitch	0.297mm
Brightness	200cd/m^2
Contrast Ratio	500:1
Resolution	1024 x 768
Response Time	8 ms
Viewing Angle	140° (horizontal) 125° (vertical)
Synchronization	75Hz
Connectivity	D-Sub 15-pin, Dual Serial/USB
Compatibility	Windows 7, Vista, XP, 2000, NT4, ME, 98, 95, XP Tablet PC, Embedded XP, Windows CE 2.13, 3.0, .net, 6.0, Debian, Fedora, Mandrake, RedHat, SuSe, Mac OS9, OSX, DOS-DOS
VESA Hole Configuration	100 x 100 mm
Voltage Rating	Embedded AC Input, 100-240V @ 50-60Hz
Power Consumption	On: 20W; Standby: 3W; Off: 1W
Dimensions (WxHxD)	350.8mm x 306.5mm x 202.0mm (with stand)
Weight	10.58lbs
Operating Temperature	32°F-104°F
Storage Temperature	-4°F-140°F
Standards	TUV, CE, UL, CUL, FCC-B, RoHS, IPX1
Limited Warranty	3 Years, Parts and Labor

Contact Us

220 Tradesmen Dr.
Hutto, Texas 78634
1.800.320.5944
sales@touchsystems.com
www.touchsystems.com

© 2012 TouchSystems